



abezeta
YOUR GLOBAL PARTNER

STRONG EUROPE

Together... Stronger!!!

JF-LTP (Series)

Litho plate corner conveyors



Corner conveyor

Turn the lateral plate from the CTP plate-making machine 90 ° into the processor which can reduce the width and cost, both with the function of machine bridge and to coordinate the height and speed difference

between the processor and platemaking machine. One CTP plate-making machine can be connected to three processors through the conveyor at the same time, improving the overall efficiency.

JF-LTP (Series)

Technical specifications

Model	JF- LTP860	JF- LTP1250	JF- LTP1650
Max. plate size (mm)	860×1100mm	1200×1500mm	1425×1650mm
Min. width (mm)	400×220mm	400×220mm	400×220mm
Speed	0-6.5m/min	0-6.5m/min	0-6.5m/min
L×W×H	1645×1300×950mm	1911×1700×950mm	2450×1900×950mm
Power	1P220V/2 A 50/60Hz		

Speciality

1. Continuously variable speed in two directions, adaptability.
2. Pneumatic lift plate, light and fast.
3. Two-stage height adjustment, meet the height difference between the processor and plate-making machine.
4. Automatically determine the position of the plate to avoid the overlapping plate into the processor.

Select Accessories

1. Two or three directions to connect the processor model.
2. Determine the plate size and send plates by the size.
3. Accept orders of special specifications or special requirements.

Carrer Valencia, 348
08009 Barcelona (Spain)
Tel. +34 934 574 504 / +34 932 075 022

info@strongeurope.com
www.strongeurope.com

abezeta
YOUR GLOBAL PARTNER



STRONG EUROPE

Together... Stronger!!!