



STRONG EUROPE

Together... Stronger!!!

abezeta
YOUR GLOBAL PARTNER

JF-TPD (Series)

Automatic thermal CTP plate processor



Computer-controlled automatic thermal ctp plate processor JF-TPD series are included steps as follow: developing, washing, gumming, drying. Unique solution cycle ways and accurate temperature control, guarantee accurate and uniform screen-point reappearance.

Speciality

1. Computer-controlled process, suitable for 0.15-0.4mm all kinds of CTP plate.
2. Solution of the liquid temperature PID control, accuracy up to $\pm 0.5^{\circ}\text{C}$.
3. Scientific solution of the circulatory system to ensure uniform temperature.
4. Developing speed, brush rotate speed is all digitally processed, stepless gear is also available.
5. Temperature setting and actual temperature clearly displayed, alarming and error-displaying also available.
6. Accurate developing liquid supply system, liquid guaranteed stable.
7. Special water-saving design, water running only when plate is moving, no more whole-process water consuming.
8. Automatic rubber roller smoothing, avoiding rubber roller drying out after long-time standing by.
9. Automatic rubber roller cleaning, avoiding rubber roller harden after long-time break.
10. Automatic alarm to remind the replacement filter system to ensure the quality of reappearance.
11. The transmission parts are with super wear-resistant materials, ensuring continuous use for three years without replacing any parts.

JF-TPD (Series)

Technical specifications

Model	SZ-TPD860	SZ-TPD1100	SZ-TPD1250	SZ-TPD1350	SZ-TPD1450	SZ-TPD1650
Max.plate width	860mm	1150mm	1300mm	1350mm	1500mm	1700mm
Dev.liter	40L	60L	60L	70L	90L	96L
Min.plate length	350mm	400mm	400mm	400mm	500mm	500mm
Plate thickness	0.15-0.4mm					
Dev.temp	15-40°C					
Dry.temp	30-60°C					
Dev.speed (sec)	15-60 sec					
Brush.speed	20-150 rpm					
Power	1P/AC220V/30A					
Net.weight	380Kg	470Kg	520Kg	570Kg	700Kg	850Kg
Machine size (mm)(online)	1370×1350×1050	1465×1640×1050	1565×1790×1050	1565×1840×1050	1660×1990×1050	1670×2190×1050
Machine size (mm)(offline)	1670×1350×1050	1760×1640×1050	1865×1790×1050	1865×1840×1050	2010×1990×1050	1970×2190×1050

Select Accessories

1. Automatic water circulation processing system.
2. Smart developer automatic replenishment system.
3. On line automatic punching and bending machine.

Carrer Valencia, 348
08009 Barcelona (Spain)
Tel. +34 934 574 504 / +34 932 075 022

info@strongeurope.com
www.strongeurope.com

abezeta
YOUR GLOBAL PARTNER



STRONG EUROPE

Together... Stronger!!!